



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 507 366 B1**

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
03.07.1996 Bulletin 1996/27

(51) Int Cl.⁶: **G06K 15/12**

(21) Application number: **92200619.2**

(22) Date of filing: **03.03.1992**

(54) **LED exposure head**

LED-Belichtungskopf

Tête d'exposition à diodes lumineuses

(84) Designated Contracting States:
BE DE FR GB

(72) Inventor: **Avonts, Kris Petrus**
B-2450 Meerhout (BE)

(30) Priority: **04.04.1991 EP 91200785**

(56) References cited:
WO-A-90/02387 **US-A- 4 875 057**

(43) Date of publication of application:
07.10.1992 Bulletin 1992/41

• **PATENT ABSTRACTS OF JAPAN** vol. 12, no. 236
(M-715)(3083) 6 July 1988 & JP-63 028 673

(73) Proprietor: **AGFA-GEVAERT**
naamloze vennootschap
B-2640 Mortsel (BE)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 507 366 B1

Description

1. Field of the invention.

5 The present invention relates to a LED (light-emitting diode) exposure head for use in a recording device for linewise recording information on a moving light-sensitive support.

Description of the prior art.

10 LED exposure heads are known that comprise an assembly in alignment of a plurality of sub-bases onto which are mounted a row of LED dice along the centre, a row of integrated circuit chips at either side of the LED dice and printed circuit boards outboard of such rows of integrated circuit chips for electrically connecting the integrated circuit chips to electrical connectors, and optical imaging means for focussing the image of the LED's onto the image plane of a photoconductor. The LED dice are electrically connected with the integrated circuit chips through so-called chip-
15 to-chip bonds, and the integrated circuit chips are in the same way connected with the circuit boards.

The sub-bases are fitted to a common base and offer the advantage that they may be completely electrically and optically tested after their assembly before they are mounted one by one on the common base.

The sub-bases are usually in the form of metal tiles of a light metal which has been gold-plated in view of a good electrical conductivity and of preventing corrosion. The LED dice, the integrated circuit chips and the printed circuit
20 boards are fitted to the sub-bases by adhesive bonding. One example of the described exposure head is disclosed in US-A 4,536,778.

These LED exposure heads cause problems with undesired light reflections on the bonding wires from the LED dice towards the integrated circuit chips, as will be described hereinafter.

Another type of LED exposure heads is known in which there are no sub-bases but instead the distinct electronic
25 components are mounted on one large ceramic substrate with printed conductor leads, the wire-bonding occurring from the LED dice to the substrate and from the substrate to the integrated circuit chips. This type of exposure head causes less problems with undesired reflections, but requires twice the number of bonding wires. Alternatively, the LED dice are directly wire-bonded to the integrated circuit chips. This technique is disclosed in JP-63 028 673.

The causes for undesired light reflections in the first type of LED exposure heads, and in more recent types in
30 particular, are as follows.

Self-focussing lenses for focussing the image of the LED's in the image plane of the photoconductor have become available with an increased depth of field. An increased depth of field leads to a better image quality but unfortunately also causes a better reproduction of undesirable light spots, such as reflections of the radiation beams of the LED's on surrounding parts of the structure.

Further, the thickness of the LED dice is still getting smaller since a smaller thickness means a shorter thermic path from the light-emitting surface to the rearside of the LED's whereby the heat-transfer for the active layer (i.e. the light-emitting layer) improves and the working temperature of said layer becomes lower. A lower temperature means more light since the temperature coefficient of a LED amounts to approximately - 0.7 %/°C. Still further, the electric series resistance is smaller as the thickness of the LED chips becomes smaller.

40 In the circumstances, it will be understood that the top surface with the bonding pads of the LED's will be located lower than the top surface with the corresponding bonding pads of the integrated circuit chips.

Since the electric wire connections from the LED's to the integrated circuit chips are made by means of highly-reflective wires, such as gold wire in the case of thermocompression bonding, or aluminium wire in the case of ultrasonic bonding; it will be understood that as such wire, and more in particular the loop in its path from one pad to the other
45 will run at a smaller angle than before with respect to a normal on the LED's, the greater will be the risk for such loop to intersect the light cone emitted by a LED and thus for undesirable reflection of light on the intersected portion of such loop.

It is possible to avoid undesired reflections of the kind described by intercepting the disturbing reflections of the image beam of the LED's. This can be done by providing an elongate diaphragm between the LED's and the lens,
50 close to the LED's. Since such diaphragm would need to have a precise slot with a width of approximately 0.5 to 1.0 mm for a length of 310 mm or more, it will be understood that it would be an expensive component, the location of which moreover would have to be very precise in order not to intercept a useful portion of the radiation beams.

SUMMMARY OF THE INVENTION

55 Object of the invention

It is the object of the invention to provide an improved LED exposure head which is not hampered by reflections

on the electric connections between the pads of the LED's and of the integrated circuit chips.

Statement of the invention

In accordance with the present invention, a LED (light-emitting diode) exposure head for use in a recording device for linewise recording information on a moving light-sensitive support, said exposure head comprising at least one metal base plate onto which are mounted a row of LED dice along the centre, a row of integrated circuit chips on at least one side of the LED dice and a printed circuit board outside of such row of integrated circuit chips for electrically connecting the circuit boards to electric connectors, the thickness of the LED dice being smaller than that of the integrated circuit chips, and optical imaging means for focussing the image of the LED's in the image plane of the light-sensitive support, is characterized in that said base plate has a raised rib for mounting the LED dice at a height above the base plate which is such that their electric bonding pads are at a level higher than that of the corresponding bonding pads of the integrated circuit chips, and wherein the paths of the wire bonded electric connections are such that they are out of contact with the light cones emitted by the LED's.

A LED exposure head with a provision that causes the underside of the LED dice to take a position that is higher than that of the base plate on which they are mounted is known from JP-A 63-28673. In this particular case, the base plate is a ceramic structure and the mentioned provision is an electrode that puts the undersides of the adjacent LED's in electrical contact. The LED's have a thickness that equals that of the integrated circuit chips.

The raised rib according to the present invention is suitably located at the centre of the base plate and has a width nearly that of the LED dice and a height such that the top of the LED dice is clearly higher than the top of the integrated circuit chips.

Since the thickness of the integrated circuit chips is larger than the thickness of the LED dice, it will be understood that the height of the mentioned rise will have to be larger than the difference in height between both components. Usual values of the height of the inventive raised ribs are between 0.2 and 1.0 mm but these values are not limitative for the present invention.

According to a suitable embodiment of the invention, the raised rib on the base is obtained by erosion-etching of a flat metal plate thereby to leave the original thickness at the centre and to reduce the thickness at the locations where the integrated circuit chips and/or the printed circuit boards will be mounted on the base.

Although a LED exposure head according to the invention may comprise only one base with a plurality of LED dice, it is clear that a head suitably comprises a plurality of LED bases in the form of sub-bases which are mounted on a common supporting base.

The term "light-sensitive support" denotes in the present specification a photoconductor drum as known in the art of electrophotographic printers, but it encompasses also photoconductive and otherwise light-sensitive supports in sheet or belt form onto which an image may be formed via exposure by a LED exposure head.

BRIEF DESCRIPTION OF THE DRAWINGS

Detailed description of the invention

The invention will be described hereinafter by way of example with reference to the accompanying drawings, wherein :

Fig. 1 is a diagrammatic view of one embodiment of the engine of a xerographic recording apparatus,

Fig. 2 is a plan view of a portion of the exposure head of the apparatus according to fig. 1,

Fig. 3 is an enlarged plan view of one LED module,

Fig. 4 is an enlarged side view of one LED module,

Fig. 5 is an enlarged view of the electric connections of a LED dice at a loop height h_1 ,

Fig. 6 is an enlarged view of the electric connections of a LED dice at a loop height h_2 , and

Fig. 7 is an enlarged side view of a prior art LED module.

Referring to fig. 1, the arrow 10 illustrates generally the engine of a xerographic printer. The term "engine" denotes the parts of the apparatus that are involved in the production of the image. A printer comprises a plurality of other parts such as a paper supply, a toner supply, a fixing station, drive means for rotation of the drum and for the paper transport, a toner fixing station, an electronic control circuit, etc. These parts are known in the art and are irrelevant for the understanding of the further description of the present embodiment of the invention.

The engine comprises a photoconductor drum 12 which may be an aluminium cylinder coated with a photosensitive photoconductor, and which is rotatable in the direction of the arrow 13. Around the drum are provided the following stations in angularly spaced relationship.

A corona-discharge station 14, which is used to uniformly electrostatically charge the surface of the drum 12.

A LED exposure head 15 for line-wise exposure of the charged surface of the photoconductor drum as its surface moves past the head.

A colour developing unit 16, which is arranged for applying coloured toner to the line-wise discharge drum surface by means of a developer sleeve 17, also called a magnetic brush.

A black-and-white developing unit 18, which is arranged for applying a black toner to the charge pattern on the drum by means of a developer sleeve 19.

A paper feed channel 20 through which a paper sheet is fed into contact with the drum for receipt of the toner image formed on the drum.

A corona transfer station 21 which applies a corona charge of a sign opposite to that of the toner to the underside of the paper to attract the toner from the drum onto the paper to form a visible, developed image.

A paper separation station 23 which applies charges to the paper so that it can be easily separated from the drum.

A paper separator 24 which functions to ensure that the paper sheet is reliably separated from the drum.

A cleaning blade 25 for scraping off residual toner left on the surface of the photoconductor drum after completion of the image transfer. This toner may be conveyed to a toner collecting bottle of the apparatus.

Finally, a main erase 26 which has a lamp 27 for neutralising any residual charge remaining on the surface of the photoconductor drum after cleaning.

In operation of the engine, the LED exposure head 15 receives a first image signal to produce on the photoconductor drum 12 a charge pattern that is developed by the black developing unit 18. The paper sheet that is removed by the separator 24 is passed through a toner fixing station which functions to melt the toner image into the paper sheet. The paper sheet is then returned by an appropriate conveying mechanism to the feed entry 20 for receiving a second toner image from the photoconductor drum, this time the colour image produced by the station 16 and by appropriate exposure by the head 15. An example of the use of the described two-colour development is that of a letter or advertising sheet, which bears a conventional black-and-white text, and the heading and/or the bottom of which bear(s) a coloured company logo.

The representation of fig. 1 shows that the different stations around the photoconductor drum are located in closely spaced relationship. Both developing stations take quite an important part of the angular space around the photoconductor drum. A unit which readily lends itself to a reduction of its angular size without impairing the satisfactory operation of the printer, is the exposure head. More details about one embodiment of a compact LED exposure head can be found in EU Pat. Appl. 90 201 779 filed 3th July, 1990 and entitled: "LED exposure head with overlapping electric circuits".

The head 15 is mounted within a housing which is composed of a base 28 and a cover 29. The base may be an extrusion-moulded component of a light metal alloy, such as aluminium, with a plurality of cooling fins at the outside and four rectangular ribs, viz. two outer 50 and two inner ribs 51 (see fig. 2) at the inside, whereas the cover has an elongate opening in which lens means 30 in the form of a Selfoc is fitted for projecting the image of the LED's of the exposure head onto a line 31 on the surface of the drum 12.

More details about a suitable construction of the housing of the exposure head can be found in EU Pat. Appl. 90 210 778, filed 3th July, 1990 and entitled: "LED exposure head".

The lay-out of the electronic circuitry of the exposure head is illustrated in the plan view of fig. 2. Said figure shows in fact three adjacent sections of the head, viz. section A being a true plan view, section B showing the base with the LED's omitted and section C showing an end section of the head.

Base 28 whose inside is turned upwardly, is provided with an elongate copper bar 32, which is fitted in the space between two inner ribs 51 of the base by means of a thermally conductive adhesive that allows minor dimensional changes of the base and of the bar, caused by the heating of these elements at operation of the exposure head.

Two elongate printed circuit strips 34 and 35 are located on the base at either side of the bar 32. The thickness of the strips is slightly less than the distance over which the bar protrudes beyond the ribs 50 and 51.

A plurality of LED modules 36 are die-bonded in closely spaced side by side relationship to the bar 28 by means of an electrically and thermally conductive adhesive, such as a silver-filled epoxy adhesive.

Each LED module is in fact an assembly of the following components on a sub-base which is constituted by a tiny metal plate 38 (see fig. 3).

A row of LED dice 39 with LED's 40, which lie along the centre of the assembly and which are cemented to the front face of the plate 38 by means of an electrically and thermally conductive adhesive. Typically, each dice is about 8 mm long and about 1 mm wide.

On each side of the row of LED dice on each plate there is a row of integrated circuit chips 41 and 42 respectively, which are equally cemented in an electrically and thermally conductive way to the base plate. The chips can comprise the drivers for the LED's, a shift register, a latch register and occasional further control and test circuits.

Outboard of the row of integrated circuit chips on each side of the centre line there are printed circuit boards in the form of a conventional thick film circuit on a ceramic base, such as 43 and 45 which are equally cemented to the

base plate. The circuit boards are connected through electric connections such as 46 with the elongate printed circuit strips 34 and 35 at connection points such as 47.

The two printed circuit strips 34 and 35 have end connectors such as 48 and 49 for bringing signals and power into the circuit.

Wire-bonded electric connections are provided between the LED dice 39 and the corresponding output pads of the integrated circuit chips 41 and 42, and between the input pads of the chips and the corresponding thick film circuits 43 and 44.

The improvement in accordance with the invention relates to the connections between the LED dice and the adjacent integrated circuit chips. This is illustrated in detail in fig. 4, which shows a side view of one LED module 36.

The module comprises a sub-base in the form of a metal plate or tile 38, which has a central raised rib 52. The described cross-sectional shape of the sub-base can be obtained in different ways, such as by die-casting, die-stamping, or milling of a plate. We have found that a very suitable technique for the production of the sub-base consists in erosion-etching a conventional flat strip of copper or the like in such a way that a central ridge of original thickness is left, but that the opposed sides are uniformly reduced in thickness to the desired amount.

LED dice 39 are cemented in a row to the front face of the sub-base by means of an electrically conductive adhesive.

Each die has near either longitudinal end of its front face a row of bonding pads 53, and 54 respectively, for the LED's. The pads have been illustrated in the figure by a short thick line on top of the LED but actually they lie in the plane of the front face of the dice. The mentioned pads are connected with corresponding bonding pads 55, 56 of the integrated circuit chips through two rows of wire-bonded electric connections 57 and 58. These connections are in the present example made by the ultrasonic bonding of an aluminium wire with a thickness of approximately 32 micrometer.

The bonding was done from the pads of the integrated circuit chips towards the corresponding pads of the LED dice.

Referring to the connections 58 by way of example, the capillary bonding tool of the bonding device is targeted on a bonding pad 56 of an integrated circuit chip 42. The tool descends bringing the free end of the wire in contact with the bonding pad. Ultrasonic energy is applied to bond the wire end, or the ball previously formed on it as the case may be, to the bonding pad. Then the tool rises to the loop height position h_1 , the clamps of the tool being open so that wire is free to feed out the end of the capillary tool. The term "loop height" means the distance the tip of the bonding tool rises above the first bond. Simultaneously with its rising, the bonding tool is displaced in the direction of the corresponding pad 54 of the LED dice 39, wire being further pulled out from the tool. Then the tool deforms the wire against the bonding pad and while ultrasonic energy is applied a wedge-shaped bond is produced. With the tool still on the bond, the clamps move backward. This pulls at the bond and the wire will break at the thinnest cross-section of the bond. The tool then rises off the LED dice, leaving the wedge bond.

The wire loops thus formed have a configuration as shown by numerals 57 and 58. The loops comprise a first portion which runs upwardly, starting from the integrated circuit chips, and a second portion which slightly descends towards the LED dice. Since radiation of the LED's occurs according to a light cone with an opening angle Alpha, it is clear that there is a good clearance between a connection 58 and the adjacent boundary of the light cone as indicated by the line 59.

A fraction only of the emitted light is transmitted by the lens 30, since the angle at which such transmission can occur is indicated by Beta. It should be noted that the relative dimensions of the different components in the drawing correspond almost with reality.

Finally, it is clear that there are also wire bonds between the integrated circuit chips 41, 42 and the corresponding thick film circuits 43, 44 but these bonds are well remote from the radiation zone of the LED's.

A detailed view of the exact configuration of the wire-bonded electric connections between the integrated circuit chips and the LED dice is shown for different loop heights in figs. 5 and 6.

Referring to fig. 5, loop height h_1 is rather limited, in the present example 0.317 mm. This has the advantage of a good separation between the wire loops 57, 58 and the light cone 59, but the disadvantage that there is no sharp bending or kink in the connection, what can be the cause of occasional rupture of the bond on the integrated circuit chip under the influence of bending stresses in the connecting wire. Therefore, a preferred bond is one as illustrated in fig. 6, where h_2 equals 0.508 mm. The increased loop height is the cause that a noticeable kink 60 is produced in the wire loops as the bonding tool is lowered after it has been positioned above the bonding pad 54. In this way, bending stresses in the wire are seriously reduced.

The problem with the electric connections between the LED dice and the integrated circuit chips in prior art LED exposure heads is described hereinafter with reference to fig. 7, in which same components received apostrophed reference numerals.

The integrated circuit chips 41', 42' being thicker than the LED dice 39', it is clear that the electric connections 57' and 58' run markedly upwardly from the LED dice towards the integrated circuit chips, which gives rise to a serious risk for a portion of the loop of these connections to intersect the light cones of the LED's as illustrated by the central portion of connection 58' intersecting boundary 59', of the light cone. A portion of the reflected light radiation, which is represented by the arrows 61, reaches the lens and is imaged on the photoconductor whereby corresponding devel-

opment and toner transfer to the final image support occurs. Radiation is also reflected by connections 57' and 58' on adjacent connections and re-reflected from such connections towards the lens.

It is possible to intercept such undesired reflections by a mask as described in the introduction of this specification. Such mask is illustrated in broken lines 62 in the drawing, but it will be understood that the construction and the location of such mask must be very precise and also remain so at heating of the exposure head in operation.

The following data illustrate the LED module described with reference to fig. 4.

Dimensions of a sub-base plate 38	14.6 × 7.9 mm
Thickness of rib 52	1.0 mm (original thickness of the plate)
Length of rib 52	7.9 mm
Width of rib 52	1.0 mm
Thickness of etched portions	0.6 mm
Thickness of LED dice 39	0.235 mm
Thickness of the integrated circuit chips	0.500 mm
Height difference between LED dice and integrated circuit chips	0.135 mm
Angle Alpha	160°
Angle Beta	24°

The invention is not limited to the described embodiment. The LED dice may comprise two staggered rows of LED's in order to increase the printing resolution.

The exposure head may comprise only one row of integrated circuit chips to drive the LED's, rather than two rows as shown.

The sub-bases may be constructed in another way than by erosion-etching, such as by die-stamping, or milling as mentioned already. The mounting means for the LED dice can also be obtained by providing a flat base plate with a central rib-like support which is fitted thereto, e.g. by soldering or brazing.

However, we have found that erosion-etching is a cheap method for manufacturing the sub-bases with good precision. Further, this technique allows the manufacturing of a plurality of sub-bases in a common supporting frame so that handling of these elements in view of the mounting of the electric components thereon, the application of the electrical bondings, etc. becomes easier.

Claims

1. A LED (light-emitting diode) exposure head (15) for use in a recording device for linewise recording information on a moving light-sensitive support, said exposure head comprising a metal base plate (38) onto which are mounted a row of LED (39) dice along the centre, a row of integrated circuit chips (41, 42) on at least one side of the LED dice and a printed circuit board (43, 44) outside of such row of integrated circuit chips for electrically connecting the circuit boards to electric connectors (48, 49), the thickness of LED dice being smaller than that of the integrated circuit chips, and optical imaging means (39) for focussing the image of the LED's in the image plane of the light-sensitive support; characterized in that said base plate (38) has a raised rib (52) for mounting the LED dice at a height above the base plate which is such that their electric bonding pads (53, 54) are at a level higher than that of the corresponding bonding pads (55, 56) of the integrated circuit chips, and wherein the paths of the wire bonded electric connections (57, 58) are such that they are out of contact with the light cones emitted by the LED's.
2. A LED exposure device according to claim 1, wherein the wire bonded electric connections (57, 58) have been made from the integrated circuit chips (41, 42) towards the LED dice (39).
3. A LED exposure device according to claim 1, wherein said base plate (38) is a metal plate which has been erosion-etched to leave a rib-like remainder (52) of original thickness on its upper surface.
4. A LED exposure device according to any of claims 1 to 3, wherein the wire bonded electric connections (57, 58) have a noticeable kink (60).
5. A LED exposure device according to any of claims 1 to 4, wherein said base plate is a sub-base plate which in its turn is mounted on a common base (28).

6. A LED exposure device according to claim 5, which comprises a plurality of adjacent sub-base plates with LED dice, which are mounted on a common base (28).
7. A LED exposure device according to claim 6, wherein said common base (28) has at the inside of the head an elongate support (32) for supporting the distinct sub-base plates (38) and at the outside a plurality of cooling fins.

Patentansprüche

1. Ein LED(Leuchtdioden)-Belichtungskopf (15) zur Verwendung in einer Aufzeichnungsvorrichtung zur zeilenweisen Aufzeichnung von Informationen auf einer beweglichen lichtempfindlichen Unterlage, wobei der Belichtungskopf eine metallene Trägerplatte (38), auf der entlang der Mitte eine Reihe von LED-Einzelchips (39), an mindestens einem Ende der LED-Einzelchips eine Reihe von IC-Chips (41, 42) und außerhalb einer derartigen Reihe von IC-Chips eine Leiterplatte (43, 44) zum elektrischen Verbinden der Leiterplatten mit elektrischen Anschlüssen (48, 49) angebracht sind, wobei die LED-Einzelchips eine geringere Stärke haben als die IC-Chips, und optische Abbildungsmittel (39) zum Fokussieren des Bildes der LEDs in die Bildebene der lichtempfindlichen Unterlage umfaßt; dadurch gekennzeichnet, daß die Trägerplatte (38) eine erhöhte Rippe (52) zum Anbringen der LED-Einzelchips in einer derartigen Höhe über der Trägerplatte aufweist, daß deren elektrische Bondkontaktstellen (53, 54) auf einem höheren Niveau liegen als die entsprechenden Bondkontaktstellen (55, 56) der IC-Chips, und wobei die Wege der drahtgebondeten elektrischen Verbindungen (57, 58) derart sind, daß sie die von den LEDs abgestrahlten Lichtkegel nicht berühren.
2. LED-Belichtungsvorrichtung nach Anspruch 1, wobei die drahtgebondeten elektrischen Verbindungen (57, 58) von den IC-Chips (41, 42) hin zu den LED-Einzelchips (39) hergestellt worden sind.
3. LED-Belichtungsvorrichtung nach Anspruch 1, wobei die Trägerplatte (38) eine Metallplatte ist, die erosionsgeätzt worden ist, um auf ihrer Oberseite einen rippenartigen Rest (52) der ursprünglichen Stärke zurückzulassen.
4. LED-Belichtungsvorrichtung nach einem der Ansprüche 1 bis 3, wobei die drahtgebondeten elektrischen Verbindungen (57, 58) einen ausgeprägten Knick (60) aufweisen.
5. LED-Belichtungsvorrichtung nach einem der Ansprüche 1 bis 4, wobei die Trägerplatte eine Teilträgerplatte ist, die wiederum auf einem gemeinsamen Träger (28) befestigt ist.
6. LED-Belichtungsvorrichtung nach Anspruch 5, die mehrere benachbarte, auf einem gemeinsamen Träger (28) angebrachte Teilträgerplatten mit LED-Einzelchips umfaßt.
7. LED-Belichtungsvorrichtung nach Anspruch 6, wobei der gemeinsame Träger (28) auf der Innenseite des Kopfs eine längliche Stütze (32) zum Abstützen der getrennten Teilträgerplatten (38) und an der Außenseite mehrere Kühllamellen aufweist.


Revendications

1. Tête d'exposition à DEL (diodes électroluminescentes) (15) destinée à servir dans un dispositif d'enregistrement pour l'enregistrement linéaire d'informations sur un support photosensible mobile, ladite tête d'exposition comprenant une plaque de base métallique (38) sur laquelle sont montées une ligne de supports de DEL (39) au centre, une ligne de puces de circuits intégrés (41, 42) sur au moins un côté des supports de DEL et une carte à circuit imprimé (43, 44) en dehors de cette ligne de puces de circuits intégrés pour connecter électriquement les cartes de circuits aux connecteurs électriques (48, 49), l'épaisseur des supports de DEL étant plus petite que celle des puces de circuits intégrés, et un moyen d'imagerie optique (39) pour focaliser l'image des DEL dans le plan d'image du support photosensible; caractérisée en ce que ladite plaque de base (38) a une nervure relevée (52) pour monter les supports de DEL à une hauteur au-dessus de la plaque de base qui est telle que leurs plages de connexion électriques (53, 54) sont à un niveau supérieur à celui des plages de connexion correspondantes (55, 56) des puces de circuits intégrés, et dans laquelle les chemins des connexions électriques par fils (57, 58) sont tels qu'elles ne sont pas en contact avec les cônes lumineux émis par les DEL.
2. Dispositif d'exposition à DEL conformément à la revendication 1, dans lequel les connexions électriques par fils

EP 0 507 366 B1

(57, 58) ont été faites depuis les puces de circuits intégrés (41, 42) vers les supports de DEL (39).

3. Dispositif d'exposition à DEL conformément à la revendication 1, dans lequel ladite plaque de base (38) est une plaque métallique qui a été attaquée par érosion pour laisser un reste de l'épaisseur d'origine en forme de nervure (52) sur sa surface supérieure.
4. Dispositif d'exposition à DEL conformément à l'une quelconque des revendications 1 à 3, dans lequel les connexions électriques par fils (57, 58) ont une coque notable (60).
5. Dispositif d'exposition à DEL conformément à l'une quelconque des revendications 1 à 4, dans lequel ladite plaque de base est une plaque de sous-base qui est à son tour montée sur une base commune (28).
6. Dispositif d'exposition à DEL conformément à la revendication 5, qui comprend une pluralité de plaques de sous-bases adjacentes avec des supports de DEL, lesquelles sont montées sur une base commune (28).
7. Dispositif d'exposition à DEL conformément à la revendication 6, dans lequel ladite base commune (28) a à l'intérieur de la tête un support allongé (32) pour supporter les plaques de sous-bases distinctes (38) et à l'extérieur une pluralité d'ailettes de refroidissement.






FIG. 2







FIG. 3






FIG. 7